

HELIUM, REFRIGERATED LIQUID Safety Data Sheet

1. IDENTIFICATION

Product identifier Product Name

HELIUM, REFRIGERATED LIQUID

Other means of identification Safety data sheet number UN/ID no. Synonyms

LIND-P061 UN1963 Helium, liquid

Recommended use of the chemical and restrictions on useRecommended UseIndustrial and professional use.Uses advised againstConsumer use

Details of the supplier of the safety data sheet

Linde Gas Singapore Pte Ltd 50 Jurong Island Highway, Singapore 627877

Phone: +65 68678998 www.linde.com.sg

For additional product information contact your local customer service.

Emergency telephone number Company Phone Number +65 68670860

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Gases under pressure	Refrigerated liquefied gas
Simple asphyxiants	Yes

Label elements



Signal word

Warning

Hazard Statements Contains refrigerated gas; may cause cryogenic burns or injury May displace oxygen and cause rapid suffocation

Precautionary Statements - Prevention Do not handle until all safety precautions have been read and understood Use and store only outdoors or in a well ventilated place Wear cold insulating gloves, face shield, and eye protection Use a backflow preventive device in piping Do NOT change or force fit connections Close valve after each use and when empty Use insulated hoses and piping to avoid condensation of oxygen-rich liquid air Always keep container in upright position

Precautionary Statements - Response IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN:. Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

Hazards not otherwise classified (HNOC) Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Volume %	Chemical Formula
Helium	7440-59-7	100	Не

4. FIRST AID MEASURES

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.	
Inhalation	Remove to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately.	
Skin contact	For dermal contact or suspected frostbite, remove contaminated clothing and flush affected areas with lukewarm water. DO NOT USE HOT WATER. A physican should see the patient promptly if contact with the product has resulted in blistering of the dermal surface or in deep tissue freezing.	
Eye contact	If frostbite is suspected, flush eyes with cool water for 15 minutes and obtain immediate medical attention.	
Ingestion	Not an expected route of exposure.	
Self-protection of the first aider	RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS.	
Most important symptoms and effects, both acute and delayed		
Symptoms	Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to oxygen-deficient atmosphere (<19.5%) may cause dizziness, drowsiness, nausea, vomiting, excess salivation, diminished mental alertness, loss of consciousness and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious injury or death. Contact with liquid may cause cold burns/frostbite.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific extinguishing methods

Continue to cool fire exposed cylinders until flames are extinguished. Damaged cylinders should be handled only by specialists.

Specific hazards arising from the chemical

Non-flammable gas. Cylinders may rupture under extreme heat.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Monitor oxygen level. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Use personal protection recommended in Section 8.
Other Information	When in contact with refrigerated/cryogenic liquids, many materials become brittle and are likely to break without warning.
Environmental precautions	

Environmental precautions	Prevent spreading of vapors through sewers, ventilation systems and confined areas.		
Methods and material for containment and cleaning up			
Methods for containment	Stop the flow of gas or remove cylinder to outdoor location if this can be done without risk. If leak is in container or container valve, contact the appropriate emergency telephone number in Section 1 or call your closest Linde location.		
Methods for cleaning up	Return cylinder to Linde or an authorized distributor. Return Portable Cryogenic Container to Linde or an authorized distributor.		
	7. HANDLING AND STORAGE		
Precautions for safe handling			
Advice on safe handling	Never allow any unprotected part of the body to touch uninsulated pipes or vessels that contain cold fluids. The extremely cold metal will cause moist flesh to stick fast and tear when one attempts to withdraw from it. Do NOT change or force fit connections. See container manufacturer's operating instructions to avoid freezing air in vent lines.		
	Liquid helium is delivered into stationary vacuum jacketed vessels at the customer's location or in vacuum-jacketted "liquid" cylinders requiring special handling methods. Consult manufacturer's instructions. Vessels for liquid helium are designed specifically for helium service. Vessels and associated structures are not designed to support higher density fluids. Density, liquid at saturation pressure at 2.7°K (-271°C) : 0.146 kg/l.		
	Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distance, use a cart designed to transport cylinders. Never attempt to lift a cylinder by its valve protection cap. Never insert an object (e.g. wrench, screwdriver, pry bar,etc.) into valve cap openings. Doing so may damage valve, causing leak to occur. Use an adjustable strap wrench to remove over-tight or rusted caps. Use only with adequate ventilation. Use a backflow preventive device in piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Ensure the complete gas system has been checked for leaks before use.		
	Never put cylinders into trunks of cars or unventilated areas of passenger vehicles. Never attempt to refill a compressed gas cylinder without the owner's written consent. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit.		
	Only experienced and properly instructed persons should handle gases under pressure. Always store and handle compressed gas cylinders in accordance with Compressed Gas Association, pamphlet CGA-P1, Safe Handling of Compressed Gases in Containers.		
	For additional recommendations, consult Compressed Gas Association's pamphlets P-1, P-9, P-9.1, P-18 and Safety Bulletin SB-2.		
Conditions for safe storage, includir	ng any incompatibilities		
Storage Conditions	Store in cool, dry, well-ventilated area of non-combustible construction away from heavily trafficked areas and emergency exits. Keep at temperatures below 52°C / 125°F. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling. Use a "first in-first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Full and empty cylinders should be segregrated. Stored containers should be periodically checked for general condition and leakage.		
Incompatible materials	None known.		
8.	EXPOSURE CONTROLS/PERSONAL PROTECTION		

Control parameters

Exposure Guidelines Appropriate engineering controls	This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies	
Engineering Controls	Ventilation systems. Local exhaust ventilation to prevent accumulation of high concentrations and maintain air-oxygen levels at or above 19.5%. Oxygen detectors should be used when asphyxiating gases may be released. Showers. Eyewash stations.	
Individual protection measures, such as personal protective equipment		
Eye/face protection	Wear safety glasses with side shields (or goggles). If splashes are likely to occur, wear:. Face-shield. Goggles.	
Skin and body protection	Work gloves and safety shoes are recommended when handling cylinders. Wear cold insulating gloves when handling liquid.	
Respiratory protection	Use positive pressure airline respirator with escape cylinder or self contained breathing apparatus for oxygen-deficient atmospheres (<19.5%).	
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Do not get in eyes, on skin, or on clothing.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Refrigerated liquefied gas
Colorless.
Odorless.
No information available
No data available
No data available
Not applicable
Not applicable
Not applicable
Not applicable
No data available
No data available
Negligible
No data available
Not applicable
No information available No data available No data available Not applicable Not applicable Not applicable Not applicable No data available Negligible No data available

Chemical Name	Molecular weight	Boiling point	Vapor Pressure	Vapor density (air	Gas Density	Critical
	_			=1)	kg/m ³ @20°C	Temperature
Helium	4.00	-268.9 °C	Above critical	0.138	0.165	-267.9 °C
			temperature			

10. STABILITY AND REACTIVITY

Reactivity Not reactive under normal conditions

<u>Chemical stability</u> Stable under normal conditions. Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Possibility of Hazardous Reactions None under normal processing.

<u>Conditions to avoid</u> None under recommended storage and handling conditions (see Section 7).

Incompatible materials None known.

Hazardous Decomposition Products None known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Product is a simple asphyxiant.
Skin contact	Contact with liquid may cause cold burns/frostbite.
Eye contact	Contact with liquid may cause cold burns/frostbite.
Ingestion	Not an expected route of exposure.
Information on toxicological effects	
Symptoms	No information available.
Delayed and immediate effects as well	as chronic effects from short and long-term exposure
Irritation Sensitization Germ cell mutagenicity Carcinogenicity Reproductive toxicity Developmental Toxicity STOT - single exposure STOT - repeated exposure Chronic toxicity Aspiration hazard	Not classified. Not classified. Not classified. This product does not contain any carcinogens or potential carcinogens listed by OSHA, IARC or NTP. Not classified. Not classified. Not classified. Not classified. Not classified. None known. Not applicable.
Numerical measures of toxicity Product Information Oral LD50 Dermal LD50 Inhalation LC50	No information available No information available No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

No known acute aquatic toxicity.

Persistence and degradability Not applicable.

<u>Bioaccumulation</u> No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to Linde for proper disposal.

14. TRANSPORT INFORMATION

DOT

UN/ID no.	UN1963
Proper shipping name	Helium, refrigerated liquid
Hazard Class	2.2
Special Provisions	T75, TP5
Description	UN1963, Helium, refrigerated liquid, 2.2
Emergency Response Guide Number	120

TDG

UN/ID no.	UN1963
Proper shipping name	Helium, refrigerated liquid
Hazard Class	2.2
Description	UN1963, Helium, refrigerated liquid, 2.2

MEX

UN/ID no.	UN1963
Proper shipping name	Helium, refrigerated liquid
Hazard Class	2.2
Description	UN1963, Helium, refrigerated liquid, 2.2

IATA

UN/ID no. Proper shipping name Hazard Class ERG Code Description

<u>IMDG</u>

UN/ID no.	
Proper shipping name	
Hazard Class	
EmS-No.	
Description	

ADR

UN/ID no. Proper shipping name Hazard Class Classification code UN1963 Helium, refrigerated liquid 2.2 2L

UN1963, Helium, refrigerated liquid, 2.2

UN1963 Helium, refrigerated liquid 2.2 F-C, S-V UN1963, Helium, refrigerated liquid, 2.2

UN1963 Helium, refrigerated liquid 2.2 3A

Tunnel restriction code	(C/E)
Special Provisions	593
Description	UN1963, Helium, refrigerated liquid, 2.2, (C/E)

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies

16. OTHER INFORMATION							
<u>NFPA_</u>	Health hazards 3	Flammability 0	Instability 0	Physical and Chemical Properties Simple asphyxiant			
Note: Ratings were assigned in accordance with Compressed Gas Association (CGA) guidelines as published in CGA Pamphlet P-19-2009, CGA Recommended Hazard Ratings for Compressed Gases, 3rd Edition.							
Issue Date Revision Date Revision Note	17-Feb-2 12-Jul-20 SDS secti						

General Disclaimer

For terms and conditions, including limitation of liability, please refer to the purchase agreement in effect between Linde Gas Singapore Pte Ltd and the purchaser.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

End of Safety Data Sheet